



IS standard



AGRIMAX FORTIS
RADIAL EXTRA LARGE TIRES



PRODUCT DATA SHEET



Radial



R-1W



E



181

Technologies



High Speed



Reinforced Carcass

Performance



Traction



High Load Capacity

Handling and Comfort



Reduced Soil Compaction

**AGRIMAX FORTIS**
RADIAL EXTRA LARGE TIRES

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil tanks to reduced compaction.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 30"	600/70 R 30	158 D/161 A8	DW 20 B	DW 18 L ; W 18 L	611	1602	724	4810	750	STD
	600/70 R 30	158 D/161 A8	DW 20 B	DW 18 L ; W 18 L	611	1602	724	4810	750	SPL
Ø 34"	600/70 R 34	160 D/163 A8	DW 18 L	DW 20 B ; W 18 L	591	1704	761	5109	800	STD
	600/70 R 34	160 D/163 A8	DW 18 L	DW 20 B ; W 18 L	591	1704	761	5109	800	SPL
Ø 38"	650/85 R 38	173 D/176 A8	DW 23 B	DW 21 B ; DW 20 B	675	2071	935	6184	975	STD
	650/85 R 38	173 D/176 A8	DW 23 B	DW 21 B ; DW 20 B	675	2071	935	6184	975	SPL
	800/70 R 38	178 D/181 A8	DW 25 B	DW 27 B	798	2085	912	6202	975	STD
Ø 42"	710/75 R 42	175 D/172 E	DW 23 B	DW 25 B	716	2133	970	6406	1000	STD
	710/75 R 42	175 D/172 E	DW 23 B	DW 25 B	716	2133	970	6406	1000	SPL

STD: Standard - SPL: Special



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index

BKT
GROWING TOGETHER