



IS standard



PAC MASTER



PRODUCT DATA SHEET



Bias



PAC MASTER

 PAC MASTER is a bias tire for compactors. It shows high stability and ensures an extended tire life-cycle. It is made of a special compound that provides particular heat resistance.

Technologies



Special Compound

Performance



Durability

Heat Resistance



Stability

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
 15"	7.50 - 15	TT	6	-	STD	225	790	-	-	6.0	6.5
	7.50 - 15	TT	12	-	STD	225	790	-	-	6.0	6.5
	7.50 - 15	TT	14	-	STD	225	790	-	-	6.0	6.5
	8.5/90 - 15 K	TL	6	-	STD	230	785	-	-	6.0	5.50 F
	9.5/65 - 15	TL	6	-	STD	235	675	-	-	7.0	-
	9.5/65 - 15	TT	6	-	STD	235	675	-	-	7.0	-
	190/60 - 15	TL	6	-	STD	186	610	291	1853	6.0	-
 16"	205/60 - 15	TL	6	-	STD	200	640	-	-	6.0 J	7.0 J
	7.50 - 16	TT	14	-	STD	225	815	-	-	6.0	6.5
	10.5/80 - 16	TL	14	-	STD	275	810	382	2480	8.0	-
 20"	10.5/80 - 16	TL	6	-	STD	275	810	382	2480	8.0	-
	9.00 - 20	TT	14	-	STD	275	1016	471	3107	7.0	7.5
	9.00 - 20	TT	16	-	STD	275	1016	471	3107	7.0	7.5
	9.00 - 20	TT	12	-	STD	275	1016	471	3107	7.0	7.5
	11.00 - 20	TT	18	-	SPL	291	1070	494	3310	8.0	8.5
	11.00 - 20	TT	16	-	SPL	291	1070	494	3310	8.0	8.5
	14/70 - 20	TT	12	-	STD	380	975	-	-	11 TG	-

STD: Standard - SPL: Special

Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference