IS standard

GROWING TOGETHER

RT 857

PRODUCT DATA SHEET

Radial

R-1

A8/B

145

Technologies

Strong Casing

Special Compound

Performance

Cut and Chip Resistance

Durability

Traction

High Load Capacity

RT 857

RT 857 is a tire designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.

	Tire size	LI/SS	RIM Rec.	RIM Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
∅ 24"	320/85 R 24 (12.4 R 24)	122 A8/B	W 11	W 10 ; W 9	329	1154	528	3449	550	STD
	380/85 R 24 (14.9 R 24)	131 A8/B	W 12	W 13 ; W 11	380	1256	566	3783	600	STD
∅ 26"	420/85 R 26 (16.9 R 26)	138 A8/B	DW 15 L	W 14 L ; W 15 L ; W 16 L ; DW 16 L	450	1374	616	4115	650	STD
	460/85 R 26 (18.4 R 26)	143 A8/B	DW 15 L	W 15 L ; W 16 L ; DW 16 L	465	1442	642	4297	675	STD
∅ 28"	320/85 R 28 (12.4 R 28)	124 A8/B	W 11	W 9 ; W 10	329	1255	577	3779	600	STD
	340/85 R 28 (13.6 R 28)	127 A8/B	W 12	W 11	353	1289	599	3908	625	STD
	380/85 R 28 (14.9 R 28)	133 A8/B	W 12	W 11 ; W 13	390	1357	617	4127	650	STD
	420/85 R 28 (16.9 R 28)	139 A8/B	W 15 L	W 14 L ; W 13	450	1425	640	4276	675	STD
∅ 30"	420/85 R 30 (16.9 R 30)	140 A8/B	W 15 L	W 14 L ; W 13	450	1476	656	4398	700	STD
	460/85 R 30 (18.4 R 30)	145 A8/B	W 16 L	W 15 L ; W 14 L	475	1544	697	4648	725	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 10-2024